




EU Type Examination Certificate CML 17ATEX2227X Issue 0


- 1 Equipment intended for use in Potentially Explosive Atmospheres Directive 2014/34/EU
- 2 Equipment **mmWAVE-is**
- 3 Manufacturer **Pulsar Process Measurement**
- 4 Address Cardinal Building,
Enigma Commercial Centre
Sandy's Road
Malvern
Worcestershire WR14 1JJ
UK
- 5 The equipment is specified in the description of this certificate and the documents to which it refers.
- 6 Certification Management Limited, Unit 1 Newport Business Park, New Port Road, Ellesmere Port CH65 4LZ, UK, Notified Body Number 2503, in accordance with Article 17 of Directive 2014/34/EU of the European Parliament and of the Council, dated 26 February 2014, certifies that this equipment has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in the confidential reports listed in Section 12.
- 7 If an 'X' suffix appears after the certificate number, it that the equipment is subject to conditions of safe use (affecting correct installation or safe use). These are specified in Section 14.
- 8 This EU Type Examination certificate relates only to the design and construction of the specified equipment or component. Further requirements of Directive 2014/34/EU Article 13 apply to the manufacture of the equipment or component and are separately certified.
- 9 Compliance with the Essential Health and Safety Requirements, with the exception of those listed in the confidential report, has been demonstrated through compliance with the following documents:

EN 60079-0:2012:A11:2013 EN 60079-11:2012
- 10 The equipment shall be marked with the following:



Ex ia IIC T4 Ga
Ta = -20°C to +80°C



Ex ia IIIC T135°C Da
Ta = -20°C to +80°C



CML 17ATEX2227X
Issue 0

11 Description

The mmWAVE-is is a DC powered level measurement sensor utilising radar technology. The sensor is housed in a non-metallic enclosure with integral five core cable which connects to control equipment located in the safe area providing power and data communication. The enclosure incorporates a threaded cap which allows the equipment to be mounted on a suitable bracket or flange.

Intrinsic safety is achieved by connecting to the non-hazardous area via intrinsically safe interface devices, and by encapsulation of the electronics and sensor.

The equipment has the following safety description:

Power Port			Signal Port			RX port			TX port		
U _i	=	28V	U _i	=	10V	U _i	=	10V	U _i	=	10V
I _i	=	120mA	I _i	=	200mA	I _i	=	200mA	I _i	=	200mA
P _i	=	0.83W	P _i	=	0.5W	P _i	=	0.5W	P _i	=	0.5W
C _i	=	5nF	C _i	=	0	C _i	=	0	C _i	=	0
L _i	=	0	L _i	=	0	L _i	=	0	L _i	=	0
						U _o	=	6.51V	U _o	=	6.51V
						I _o	=	208mA	I _o	=	208mA

12 Certificate history and evaluation reports

Issue	Date	Associated report	Notes
0	2 Nov 2017	R11292A/00	Issue of prime certificate

Note: Drawings that describe the equipment or component are listed in the Annex.

13 Conditions of manufacture

The following conditions are required of the manufacturing process for compliance with the certification.

- 13.1 Where the product incorporates certified parts or safety critical components the manufacturer shall ensure that any changes to those parts or components do not affect the compliance of the certified product that is the subject of this certificate.

14 Special Conditions for Safe Use (Conditions of Certification)

The following conditions relate to safe installation and/or use of the equipment.

- 14.1 Under certain extreme circumstances, the non-metallic parts incorporated in the enclosure of this equipment may generate an ignition-capable level of electrostatic charge. Therefore, the equipment shall not be installed in a location where the external conditions are conducive to the build-up of electrostatic charge on such surfaces. This is particularly important if the equipment is installed in a zone 0 location. In addition, the equipment shall only be cleaned with a damp cloth
- 14.2 The equipment must be routinely inspected to avoid the build up of dust layers when installed in a Zones 20, 21, or 22.



CML 17ATEX2227X
Issue 0

- 14.3 The equipment must only be connected to resistive intrinsically safe sources with minimum resistances as follows
- Power connection $R \geq 234\Omega$
 - Signal connection $R \geq 50\Omega$
 - TX connection $R \geq 50\Omega$
 - RX connection $R \geq 50\Omega$
- 14.4 When installing the equipment, the installer shall consider the length of integral cable attached to the equipment, in addition to any externally installed cable. The integral cable shall be considered to have parameters of 200pF/m, and 1 μ H/m or 30 μ H/ Ω

Certificate Annex

Certificate Number CML 17ATEX2227X
Equipment mmWAVE-is
Manufacturer Pulsar Process Measurement



The following documents describe the equipment or component defined in this certificate:

Issue 0

Drawing No	Sheets	Rev	Approved date	Title
D-804-1221-B	1 of 1	B	2/11/2017	mmWAVE dBR16 Radar hazardous area protection
D-804-1264-A	1 to 2	A	2/11/2017	mmWAVE dBR16 Protection PCB layout
D-804-1246-A	1 of 1	A	2/11/2017	mmWAVE dBR16 Protection V1.0 Haz area schematic
D-804-1243-A	1 of 1	A	2/11/2017	mmWAVE dBR16 radar module
D-804-1242-A	1 of 1	A	2/11/2017	mmWAVE-is dBR16 Exia wraparound label
D-804-1197-E	1 of 1	E	2/11/2017	mmWAVE dBR16 Radar general arrangement
D-804-1240-B	1 of 1	B	2/11/2017	mmWAVE dBR16 Radar housing base
D-804-1261-A	1 to 4	A	2/11/2017	mmWAVE dBR16 CPU PCB layout
D-804-1260-A	1 to 2	A	2/11/2017	mmWAVE dBR16 CPU V1.1 Haz area schematic
D-804-1244-B	1 of 1	1	2/11/2017	mmWAVE dBR16 Radar cable assembly Exia
D-804-1238-A	1 of 1	A	2/11/2017	mmWAVE dBR16 Radar cap BSP
BOM-0020-A	1 of 1	1.1	2/11/2017	Controlled Bill of Materials mmWAVE dBR16 Exia
A-301-0163-A	1 of 1	1.0	2/11/2017	mmWAVE dBR16 Protection V1.0 hazardous area BOM
D-804-1239-A	1 of 1	A	2/11/2017	mmWAVE dBR16 Radar cap NPT
D-804-1230-B	1 of 1	B	2/11/2017	mmWAVE dBR16 Polysulfone dome